



Eva - Emp 2.0



Flexi Temp



Easy Slide Out



3 Way Pay

## Corallo 1700

### Description

Corallo 1700 is the new generation of 6-spirals snack&food vending machines with 5 and 6 removable trays for dispensing snacks, cold beverages in cans or bottles and, in the food version (1°C - 4°C), also sandwiches and fresh products.

The great versatility of configurations allows to create different combinations to offer a wide range of products.

Can be perfectly combined with freestanding hot drinks vending machine Cristallo 400 with base unit kit. Also available in Slave version, without payment systems slot, to be combined with freestanding hot Cristallo 400 using relative kit.

### Accessories

- Photocell kit
- Memory key to copy and quickly transfer machine settings
- Interface kit for USB key
- Eva-Dts kit with serial connection
- Eva-Dts kit with infrared connection
- Product compartment reinforcement kit
- Wall-mounting brackets kit

### Main features

- Energy consumption in A class according to EVA - EMP 2.0
- Programmable temperature based on product assortment (Saeco Flexi Temp)
- The extraction of the refrigerating unit is very easy, through 2 screws and 2 knobs, and facilitated by slideways (Saeco Easy Slide Out)
- Possibility to install 3 payment systems on the door at the same time (Saeco 3 Way Pay) - (not on Slave version)
- Accepts the most commonly used parallel and serial MDB, BDV and Executive payment systems (possible Master and Slave configurations) - (not on Slave version)
- Personalisation of the spiral and tray configuration
- In the slave version the machine is without the slot (and consequently without payment systems, CPU, etc.) and it is managed by the hot machine

### User interface

- 9-button keyboard (not on Slave version)
- 2-line, 20-character alphanumeric display (not on Slave version)

**Technical data**

**Corallo 1700**

**Structural specifications**

Dimensions (w x h x d)	765 x 1700 x 900 mm (600 x 1700 x 900 mm - Slave version)
Weight	248 kg (205 kg - Slave version)

**Electrical specifications**

Power supply	230 V/50 Hz
Power consumption	600 W

**Other specifications**

Number of trays	5 - 6
Bottle tray	36 bottles Ø 69 mm, h 210 mm
Can tray	36 cans
Snack tray	according to the spiral type
Number of spirals	36 - 42
Available spirals	17 (27 products) to 90 (5 products) pitch
Refrigerating unit	1/5 HP
Adjustable temperature	
Stratified configuration snack/can/bottle	7°C - 14°C throughout the cell
Configurazione food snack food/Tetra Pak	7°C - 14°C 3-4 upper trays 1°C - 4°C 3 lower trays
Ecological refrigerant fluid	R 404a

**Technical specifications**

- Programmable temperature based on product assortment (Saeco Flexi Temp)
- Health control to block the dispensing of products if the temperature is not adequate
- Refrigerating unit in monoblock consisting of a plate base on which all components are set. The extraction of the group is very easy, through 2 screws and 2 knobs, and facilitated by slideways (Saeco Easy Slide Out).
- The removable slot allows the maintenance of the machine without interacting with the refrigerated area. The slot supports CPU, payment systems, display, keyboard and closes the coin box area (not on Slave version).
- Automatic defrost cycles thanks to the anti-frost probe
- Painted steel-sheet body with polystyrene foam sheets insulation. Thanks to this structure the chassy can be disassembled.
- Drawn-aluminium door with anti-condensate resistance selectable electronically. The insulation on the door locking is secured by a magnetic bellows-seal.
- Double-layer safety glass with insulation cushion equipped with anti-condensate resistance selectable electronically
- Height of the cell containing the trays equal to 1140 mm
- The tilting product dispensing tray allows an easy extraction of the first tray at the bottom for loading, has a plastic structure that supports the push and anti-theft doors
- Removable plastic trays, which provide a suitable resistance to weight. The tray position can easily be adjusted with 30 mm shifts.
- Self configuration with automatic reset at every machine start
- Programming sale prices (up to 25)
- 5-button keypad with direct access to functions useful for the operator
- Programmable Rielta lock
- Simple failure reset
- General safety relay for 24 V components
- Thermal cut-outs on all devices supplied with line voltage
- CE and VDE approved



**Corallo 1700**  
+  
**Cristallo 400**



**Corallo 1700 Slave**  
+  
**Cristallo 400 Master**