




LEI600



ECONOMIES AND TECHNOLOGIES ARE NO LONGER INCOMPATIBLE.

LEI600, automatic vending machine for hot drinks with 600 cups capacity. Designed to easily interchange the push-button panel and adapt to different locations.



LEI600 TOUCH 21"



LEI600 SMART + ARIA L MASTER

USER INTERFACE

▪ Great modularity with 3 interchangeable user interfaces:

Easy: standard membrane keypad, with 24 large buttons.

Smart: touchscreen saw technology selection panel (surface acoustic wave), with 24 wide backlit selections.

Touch: monitor 21,5" with touch screen technology able to play multimedia contents.

- Customizable sugar dosage.
- End selection acoustic signal.
- 32 digit alphanumeric LCD displays.
- Slow falling product dispensing door.

Bianchi Vending



CUP
SENSOR
DETECTION
(OPTIONAL)



LED, LOW
VOLTAGE
LIGHTING



PATENTED
ESPRESSO
GROUP



VARIABLE
CHAMBER
COFFEE
BREWER



ENERGY
SAVING
MODE
(OPTIONAL)

SPECIFICATIONS

- ELECTRICAL SUPPLY: 230 Vac – 50 Hz
 - INTERNAL ELECTRICAL SUPPLY
- All the electrical components are supplied at 24 Vdc, with the exception of the boiler resistances, the pump and the steam ventilator that are at powered by the mains voltage.
- POWER SUPPLY
- 1.80 kW espresso version single boiler
2.25 kW instant version
- WATER SUPPLY: Fitting connection = 3/4"
- Water pressure = 0.5 – 6.5 bar

FEATURES

- Version with traditional espresso brewer: espresso coffee made in compliance with Italian tradition.
- Version with variable chamber coffee group (ESV): doses from 7 to 14 gr. Ensures optimum pressing and brewing conditions.
- Reinforced cabinet with anti-vandal hinges and door lock with programmable code.
- Mixers and boiler assembly are extractable to make maintenance operations easier.
- Standard serpentine kit for tea on all versions.
- Cup dispenser adjustable to various diameters (from 70 to 71 mm) and dispenser for 90 or 105 mm stirrers.
- Switching power supply that guarantees total stability of the instant product dose and complete electric safety protections.
- Standard multi-protocol electronics.
- Compatible with telemetry.

PAYMENT SYSTEM

- Compatible with all payment systems available on the market.
- Can work in master/slave with only one set of payment system on the hot vending machine together with a refrigerated automatic spiral vending machine for the sale of snacks, cans and bottles.

PRODUCT CAPACITY

Coffee beans*	3.50 kg
Decaffeinated coffee	0.70 kg
Barley	0.75 kg
Milk	2.20 kg
Creamer	4.00 kg
Chocolate	4.80 kg
Lemon tea	5.20 kg
Tea	2.40 kg
Soup	3.80 kg
Sugar	5.20 kg
Stirrers**	600 pcs.
Cups	600/700 pcs.

* Fitting an extension can catch up with 4.50 kg.
** Available only on Espresso coffee version.

ACCESSORIES KIT


- Cup sensor to reduce the consumption of plastic cups and to deliver a beverage in a mug.
- Conversion kit Lei600 Easy or Smart in Touch21".
- Conversion kit Lei600 Easy in Smart.
- Conversion kit Lei600 Smart in Easy.
- Vandal-proof coin introduction kit.
- Kit clock chip (for energy saving mode and promotional activities).
- Side dispenser housing 6 trays with 2 spirals for the distribution of mini-snacks that can be combined with the selected drink. And for tea lovers, spirals can also dispense a wide variety of tea bags.

ENVIRONMENT

- Backlighted lexan with led to reduce energy consumption and with a lifetime greater than neon.
- Compatible with paper cups and wooden stirrers.
- Energy Saving Mode to reduce the energy consumption when the machine is in stand by.
- In compliance with **ROHS** and **WEEE**.


VERSIONS LEI600 EASY SMART TOUCH	ESPRESSO 1ES-6 SINGLE BOILER	ESPRESSO 1ESV-6 SINGLE BOILER	INSTANT IN-8
TRADITIONAL ESPRESSO GROUP	✓	-	-
VARIABLE CHAMBER COFFEE GROUP (ESV)	-	✓	-
COFFEE BEAN CANISTERS	1	1	-
INSTANT CANISTERS (SUGAR INCLUDED)	6	6	8
DIMENSIONS MM	1830*H x 620W x 735D / WEIGHT 155 KG * + 5 mm upper plate		

1. Sugar 2. Instant 3. Instant 4. Coffee beans
5. Chocolate 6. Milk 7. Tea



ESPRESSO

1. Tea 2. Decaffeinated 3. Vanilla coffee 4. Coffee
5. Sugar 6. Soup 7. Chocolate 8. Milk



INSTANT